

Technical Data Sheet

ProLung Test™ Kit PL2000

For single use with the ProLung Test®

Packaging:	1073B Tyvek / 35793-E Film / Self-Seal Tape
Shelf life:	24 months from date of manufacture
Storage and Operation Temp:	-10° to 32°C
Humidity:	Equipment not to be exposed to humidity For extended periods of time. Store and transport in dry, indoor locations only.



ProLung Test Kit® contains:

6 x Diaphoretic Monitoring Electrodes TK-E5-0001

Gel:	10% Potassium Chloride (KCl) Wet Gel
Basepad:	Closed cell polyethylene foam
Basepad size:	5.1 cm diameter
Adhesive:	Medical grade acrylic adhesive
Snap:	316 L stainless steel
Sensor:	Silver / silver chloride (Ag/AgCl) plated plastic
Packaging:	Hermetically sealed paper/foil laminate
Special features:	Latex free
Application temp:	Ambient temperatures




1 x ProLung Test Key TK-J5-0004

Version:	USB 2.0
Storage:	64 MB
Dimensions:	0.7 x 2 x 0.75 cm
Packaging:	Low-density polyethylene




1 x Probe Tip and Introducer BP-E5-1391, BP-E4-1450

Probe Tip:	360 Brass
Length:	12 mm
Diameter:	6 mm
Introducer:	Polyethylene



1 x Sponge TK-E5-0002

Packaging:	Low-density polyethylene
Sponge:	Polyurethane foam
Dimensions:	5.6 cm diameter
Special features:	Latex-free and hypoallergenic
Packaging:	Low-density polyethylene



757 E South Temple, Ste 150
Salt Lake City, UT 84102 USA

+1.801.736.0729

www.prolunginc.com



*CE 0120, approved for sale in Europe (EEA & EFTA)
Not currently available for sale in the USA.